



SGE2010

## Ethernet Switch with 48-Port 10/100/1000 and 4 Shared SFP Slots

The Linksys SGE2010 Managed switch with WebView allows you to expand your network securely. Configuration of the switch is secured using SSL for Web access.

The SGE2010 is optimized for maximum system availability with fully-redundant stacking, redundant power options, and dual images for resilient firmware upgrades. The switch secures the network through IEEE 802.1Q VLANs, IEEE 802.1X port authentication, Access Control Lists (ACL), DOS Prevention, and MAC-based filtering. The enhanced QoS and traffic-management features ensure clear and reliable voice and video communications.

The SGE2010 provides resilient stacking for up to 4 units, or 192 ports. A stack of units is managed as a single switch with one web management interface. The SGE2010 can coexist in a stack with Linksys SGE2xxx/P 24-port and 48-port switches such as the Linksys SGE2000, SGE2000P, and SGE2010P, for a maximum of 192 ports in a stack. The stacking functionality includes master/backup unit behavior, ring and chain architecture, and hot insertion and removal of units.

The SGE2010 switch provides an intuitive, secure management interface enabling you to better utilize the comprehensive feature set of the SGE2010, resulting in a better optimized, more secure network.

Optimized for the network core with 48 Gigabit ports and redundant power

Fully-resilient stacking provides optimized growth with simplified management

Secure management via SSH/SSL and secure user control via 802.1x and MAC filtering

Maximum security and control of traffic with policing, shaping, ACLs, and QoS

**PRODUCT DATA**

# 48-Port Gigabit Ethernet Switch

Model: **SGE2010**

**BUSINESS SERIES**

## Features

- 48 - 10/100/1000 Ethernet ports
- 4 mini-GBIC slots (shared with 4 Ethernet ports) for fiber Gigabit Ethernet expansion
- Dual images for resilient firmware upgrades
- 96 Gbps, non-blocking, store-and-forward switching capacity
- Simplified QoS management using 802.1p, Diffserv or ToS traffic prioritization
- Power redundancy when used with the RPS1000 Redundant Power Supply unit
- Fully-resilient stacking provides optimized growth with simplified management
- Access Control Lists (ACLs) for granular security and QoS implementation
- Configuration and monitoring from a standard web browser
- Secure remote management of the switch via SSH and SSL encryption
- 802.1q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN edge simplifies network isolation for guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through GVRP/GARP

## PRODUCT DATA

## BUSINESS SERIES

# 48-Port Gigabit Ethernet Switch

## Specifications

Model	SGE2010 48-Port 10/100/1000 Ethernet Switch
Ports	48 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T with 4 Gigabit combo ports shared between mini-GBIC ports; console port; auto MDI/MDI-X; autonegotiate/manual setting; RPS port for connecting to redundant power supply unit
Buttons	Reset button
Cabling Type	UTP CAT 5 or better for 10BASE-T/100BASE-TX; UTP CAT 5e or better for 1000BASE-T
LEDs	PWR, Fan, Link/Act, Speed, RPS, Master, Stack ID 1 - 8

## Performance

Switching Capacity	96 Gbps non-blocking
Forwarding Capacity	71.4M packets per second (64-byte packets)

## Stacking

Stack Operation	Up to 192 ports in a stack Hot insertion and removal Ring and chain stacking options Master and backup master for resilient stack control Auto-numbering or manual configuration of units in stack
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Layer 2

MAC Table Size	8K
Number of VLANs	256 active VLANs (4096 range)
VLAN	Port-based and 802.1q tag-based VLANs; protocol-based VLAN; management VLAN; multicast TV VLAN; private VLAN Edge (PVE); GVRP
HOL Blocking	Head-of-line blocking prevention

## Layer 3

Layer 3 Options	Static routing; Classless Interdomain Routing (CIDR); 60 static routes; IPv4 and IPv6; Forwarding in silicon - wire-speed forwarding of Layer 3 traffic
-----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------

## Management

Web User Interface	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
SNMP	SNMP version 1, 2c, and 3 with support for traps
SNMP MIBs	RFC1213 MIB-2, RFC2863 Interface MIB, RFC2665 Ether-like MIB, RFC1493 Bridge MIB, RFC2674 Extended Bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1, 2, 3, and 9 only), RFC2737 Entity MIB, RFC 2618 RADIUS Client MIB, RFC 1215 Traps
Remote Monitoring (RMON)	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis)
Firmware Upgrade	Web browser upgrade (HTTP/HTTPS) and TFTP Dual images for resilient firmware upgrades
Port Mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe.
Other Management	Traceroute; single IP management; SSL security for web user interface; Secure Shell (SSH); RADIUS; port mirroring; TFTP upgrade; DHCP client; BootP; SNMP; Xmodem upgrade; cable diagnostics; PING; syslog; Telnet client (SSH secure support)

## Security

IEEE 802.1x	802.1x - RADIUS authentication, MD5 Hash; guest VLAN; single/multiple host mode
Access Control Lists (ACLs)	Drop or rate limit based on source and destination MAC or IP address, protocol, port, VLAN, DSCP/IP precedence, TCP/UDP source and destination ports, 802.1p priority, Ethernet type, ICMP packets, IGMP packets, DHCP snooping, ARP inspection, and IP source address guard Up to 1018 rules

## Availability

Link Aggregation	Using IEEE 802.3ad LACP, up to 8 ports in up to 8 groups
Storm Control	Broadcast, multicast and unknown unicast
DOS prevention	DOS attack prevention

- User/Network port-level security via 802.1x authentication and MAC-based filtering
- Increased bandwidth and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate-limiting capabilities, including back pressure and multicast, broadcast, and flood control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo Frame support up to 10KB
- SNMP v1, v2c, v3 and RMON support
- Fully rack-mountable using included rack-mounting hardware

Spanning Tree	IEEE 802.1D Spanning Tree, IEEE 802.1w Rapid Spanning Tree, IEEE 802.1s Multiple Spanning Tree, and fast linkover
IGMP (version 1 and 2) Snooping	Limits bandwidth-intensive multicast traffic to only the requestors and supports 256 multicast groups
Power Redundancy	Connection to RPS unit for power redundancy
<b>Quality of Service</b>	
Priority Levels	4 hardware queues
Scheduling	Priority queuing and weighted round robin (WRR)
Class of Service	Port-based; 802.1p VLAN priority-based; IPv4/v6 IP Precedence/TOS/DSCP-based; Diffserv; Classification and Re-marking ACLs
Rate Limiting	Ingress policer; egress rate control; per VLAN
Statistics	16 meters

### Standards

802.3 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x Flow Control, 802.3ad; 802.1D STP, 802.1Q/p VLAN, 802.1w Rapid STP, 802.1s Multiple STP, 802.1x Port Access Authentication

### Environmental

Dimensions	17.32" x 14.70" x 1.73" (440 x 375 x 44 mm)
Weight	10.89 lb (4.94 kg)
Power	100-240V 47-63Hz, Internal, Universal; also equipped with external redundant power supply connector for external power supply, -48VDC
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47)
Operating Temp.	32 to 104°F (0 to 40°C)
Storage Temp.	-4 to 158°F (-20 to 70°C)
Operating Humidity	10 to 90%, relative, non-condensing
Storage Humidity	10 to 95%, relative, non-condensing

### Package Contents

- One SGE2010 Ethernet Switch
- One AC power adapter with power cord
- Two rack-mounting kits with 8 screws
- One CD-ROM with user documentation (PDF) included
- One registration card
- Console cable

### Minimum Requirements

- Web browser—Mozilla Firefox version 1.5 or later; Microsoft Internet Explorer version 5.5 or later
- Cat5 Ethernet Network Cable
- TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in the network
- Provider support for CPE software version 1.2 or higher

Linksys  
A Division of Cisco Systems, Inc.  
121 Theory  
Irvine, CA 92617 USA

E-mail: sales@linksys.com  
Web: www.linksys.com

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our worldwide website at www.linksys.com

## PRODUCT DATA

## BUSINESS SERIES

Check the product package and contents for specific features supported. Specifications are subject to change without notice.



Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2008 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.

8031010NC-KO

Model: **SGE2010**

**LINKSYS**<sup>®</sup>  
A Division of Cisco